

DSO-200Mini handheld oscilloscope



| MAIN FEATURES | |
|----------------|---|
| Functions | Digital oscilloscope |
| Stand function | Integrated 90° foldable stand |
| Battery | 1000 mAh lithium battery, re- chargeable via USB-C (5 V / 1 A) |
| Display | 2,8" 320x240 LCD Display |
| Documentation | Included manual in German, English, Spanish, Italian and French |
| | |

AAIN EEATUDEC

Experience precise measurement accuracy and portability like never before with our new DSO-200 handheld oscilloscope. Designed for hobby electronics engineers who value precision and portability, the DSO-200 puts top performance in your hands.

The DSO-200 fits comfortably in your hand and stores easily in your workshop or on your desk, thanks to its foldable stand and compact, rugged design. The ease of use and portability make the DSO-200 your perfect companion.



| TECHNICAL SPECIFICATIONS | | |
|------------------------------|--|--|
| Sampling rate | 2,5 MS/s | |
| Bandwidth | 200 kHz | |
| Vertical sensitivity | 10 mV/Div - 20 V/Div | |
| Horizontal time base | 10 μs/Div - 50 s/Div | |
| Test voltage range | X1: 80 Vpp (-40 V - 40 V) X10: 800 Vpp (-400 V - 400 V) | |
| Trigger modes | Auto, normal, single | |
| Coupling | AC, DC | |
| Calibration (Square wave) | Frequency: 1 kHz Duty cycle: 50% | |

| ADDITIONAL INFORMATION | |
|------------------------|---|
| Items shipped | DSO-200, USB-C cable, hand strap, oscilloscope probe, test clip with crocodile clamps, BNC adapter, manual |
| Dimensions | 99 x 69 x 20 mm |
| Article no. | DSO-200 |
| EAN | 4250236826172 |
| Customs tariff no. | 90302000 |

Published: 2023.10.13